FLOS

Mounting : Floor Lamps description : I × MAX 120W E27 PAR38 + I × MAX 100W E27 HSGS Environment : Indoor Finish : Silver Technical description : Floor lamp providing indirect and diffused light. Silver powder-coated steel base. Opaline extruded polymethylmethacrylate (PMMA) diffuser column. Functions ON/OFF of two placed luminous sources at the extremities of the diffuser of the apparatus, happen by means of interrupting double quantity to paced luminous sources at the extremities of the cable feeding electrical worker. Stylos ELECTRICAL Emergency : Without Stylos Switching : Functions ON/OFF happen by means of interrupting double quantity to pedal mounted on the cable feeding electrical worker. Floor lamp providing indirect and diffused light Voltage (V) : 230 •F63 10004 Silver PHYSICAL : Silver •F63 10004 Silver Supply : Power cord : CCE @@ [P]	STYLOS			
Environment : Indoor Finish : Silver Technical description : Floor lamp providing indirect and diffused light. Silver powder-coated steel base. Opaline extruded polymethylimethacrylate (PMAA) diffuser column. Functions ON/OFF of two placed luminous sources at the extremities of the diffuser of the apparatus, happen by means of interrupting double quantity to pedal mounted on the cable feeding electrical worker. Stylos ELECTRICAL Emergency : Without Stylos Switching : Functions ON/OFF happen by means of interrupting double quantity to pedal mounted on the cable feeding electrical worker. Floor lamp providing indirect and diffuser dight. Voltage (V) : 230 •F6310004 Silver PHYSICAL : Supply : Power cord •F6310004 Silver Supply : Power cord : 2850 : §9.6	Mounting	: Floor		
Finish : Silver Technical description : Floor lamp providing indirect and diffused light. Silver powder-coated steel base. Opaline extruded polymethylmethacrylate (PMMA) diffuser column. Functions ON/OFF of two placed luminous sources at the extremities of the diffuser of the apparatus, happen by means of interrupting double quantity to pedal mounted on the cable feeding electrical worker. Stylos ELECTRICAL Emergency : Without Stylos designed byAchille Castiglioni Switching : Functions ON/OFF happen by means of interrupting double quantity to pedal mounted on the cable feeding electrical worker. Floor lamp providing indirect and diffused light. Voltage (V) : 230 • F6310004 Silver PHYSICAL : Power cord Silver • F6310004 Silver Weight (kg) : 9.6	Lamps description	: I x MAX 120W E27 PAR38 + I x MAX 100W E27 HSGS		
Technical description : Floor lamp providing indirect and diffused light. Silver powder-coated steel base. Opaline extruded polymethylmethacrylate (PMMA) diffuser column. Functions ON/OFF for two placed luminous sources at the extremities of the diffuser of the apparatus, happen by means of interrupting double quantity to pedal mounted on the cable feeding electrical worker. Stylos ELECTRICAL Emergency : Without Stylos Switching : Functions ON/OFF happen by means of interrupting double quantity to pedal mounted on the cable feeding electrical worker. Floor lamp providing indirect and diffused light Voltage (V) : 230 Floor lamp providing indirect and diffused light Silver PHYSICAL Supply : Power cord Silver Cond length(mm) : 2850 Construction material : Polymethylmethacrylate, Steel IP Weight (kg) : 9.6 IP IP	Environment	: Indoor		
powder-coated steel base. Opaline extruded polymethylmethacrylate (PMMA) diffuser column. Functions ON/OFF of two placed luminous sources at the extremities of the diffuser of the apparatus, happen by means of interrupting double quantity to pedal mounted on the cable feeding electrical worker. Stylos ELECTRICAL Emergency : Without Stylos Switching : Functions ON/OFF happen by means of interrupting double quantity to pedal mounted on the cable feeding electrical worker. Floor lamp providing indirect and diffused light Voltage (V) : 230 • F6310004 Silver PHYSICAL Supply : Power cord Supply : Polymethylmethacrylate, Steel Weight (kg) : 9.6 IP IP	Finish	: Silver		
ELECTRICAL Floor lamp providing indirect and diffused light Emergency : Without Switching : Functions ON/OFF happen by means of interrupting double quantity to pedal mounted on the cable feeding electrical worker. Voltage (V) : 230 PHYSICAL •F6310004 Supply : Power cord Cord length(mm) : 2850 Construction material : Polymethylmethacrylate, Steel Weight (kg) : 9.6	·	powder-coated steel base. Opaline extruded polymethylmethacrylate (PMMA) diffuser column. Functions ON/OFF of two placed luminous sources at the extremities of the diffuser of the apparatus, happen by means of interrupting double quantity to pedal mounted on the cable feeding electrical		e Castiglioni
Switching : Functions ON/OFF happen by means of interrupting double quantity to pedal mounted on the cable feeding electrical worker. Floor lamp providing indirect and diffused light Voltage (V) : 230 • F6310004 Silver PHYSICAL Supply : Power cord • F00 relamp providing indirect and diffused light Supply : Power cord • F6310004 Silver Cord length(mm) : 2850 • F6310004 Silver Weight (kg) : 9.6 • F0 • • • • • • • • • • • • • • • • • • •				
double quantity to pedal mounted on the cable feeding electrical worker. Voltage (V) : 230 PHYSICAL Supply : Power cord Cord length(mm) : 2850 Construction material : Polymethylmethacrylate, Steel Weight (kg) : 9.6	• •			
PHYSICAL Supply : Power cord Cord length(mm) : 2850 Construction material : Polymethylmethacrylate, Steel Weight (kg) : 9.6	Switching	double quantity to pedal mounted on the cable		
Supply : Power cord Cord length(mm) : 2850 Construction material : Polymethylmethacrylate, Steel Weight (kg) : 9.6	Voltage (V)	: 230	F6310004	Silver
Cord length(mm) : 2850 Construction material : Polymethylmethacrylate, Steel Weight (kg) : 9.6	PHYSICAL			
Construction material : Polymethylmethacrylate, Steel Weight (kg) : 9.6	Supply	: Power cord		
Construction material : Polymethylmethacrylate, Steel Weight (kg) : 9.6	Cord length(mm)	: 2850		
	Construction material	: Polymethylmethacrylate, Steel		
	Weight (kg)	: 9.6	IP	





