
Wohlert





Design: Vilhelm Wohlert

Concept: The fixture provides uniform, general and diffuse illumination. The opening at the bottom of the glass produces downwards directed light. The quality of the glass ensures that the fixture is evenly lit.

Finish: Matt white opal glass.

 $\label{thm:matt} \textbf{Material: Shade: Mouth-blown matt white opal glass. Pendant tube: Brushed steel.}$

Mounting: Suspension type: Cable 3x0,75mm². Canopy: Yes. Cable length: 3m.

Weight: Max. 4.5kg.

Class: Ingress protection IP20. Electric shock protection I w. ground.

Product code	Dimensions	Light source	Finish	Cable type	Lighting control
SATE-P	Ø 250	1x26W TC-TEL GX24q-3 HF	WHT OPAL GLASS	WHT PL	NOT APPLICABLE
	Ø 300	1x26/32W IC-IEL GX24q-3 HF		WHI IEX	UM 1-10V
	Ø 350	1x26W/32W/42W IC-TEL HF			
	Ø 400	1x26W/32W/42W IC-IEL HF-D			
		1x200W E27			
		1x26/32W IC-IEL G24q-3 HF-D			

Specification notes 26/32W TC-TEL only available with Ø 300. 26/32/42W TC-TEL only available with Ø 350 and Ø400. The innovation of light sources is ongoing. Consequently we only inform about the max. wattages. On www.louispoulsen.com we update a list of recommendable light sources.

