

SASSO 80 K OFFSET

EINBAUSTRÄHLER RECESSED SPOTLIGHTS FARETTI DA INCASSO

46



D

Strahlerelement aus Aluminium, 355° dreh-, 45° schwenkbar
Ruhiges Deckenbild durch zurückversetztes Strahlerelement
Set für randlosen Einbau in Gipskartondecken 8-25mm
Einbauung für Zwischendecken von 2-25mm
Durch Patentkugelschnapper werkzeuglos einsetzbar
Betriebsgeräteanschluss der HIT Varianten mittels Stecker
Variante mit energieeffizienten e² LEDs 1,1W mit hoher Farbwiedergabe
Farbfilter, Linsen, Wabenraster (max. 1 Stk.) und RGB-LED Einsatz als Zubehör


E

Spotlight made of aluminium, 355° rotatable, 45° tiltable
Calm ceiling scene by using offset spotlight
Mounting set for trimless install. in plasterboard ceilings 8-25mm
Mounting ring for ceilings from 2-25mm
Patented ball catch system installs without tools
Plug connection for control gear of HIT type
Type with energy efficient e² LEDs 1,1W with high CRI
Colour filters, lenses, louvers (max. 1) and RGB-LED inset available as acc.


I

Faretto in alluminio, girevole 355°, orientabile 45°
Impressione tranquilla grazie al faretto arretrato
Set da montaggio a livello in soffitti di cartongesso 8-25mm
Anello di montaggio per controsoffitti di 2-25mm
Inseribile facilmente con brevettato moschettone sferico
Varianti HIT: Connettore per collegare il reattore
Variante con LED e² da 1,1W con resa cromatica alta
Filtri colorati, lenti, reticoli a nido d'ape e inserti RGB come acc.


Type



SASSO 80 K SPOTLIGHT LED 24V DC	
e² LED	CODE
CAPACITY	052-1310#1#M
3x1,1W	
052-...4_	2700K 89 lm/led
5_	3000K 89 lm/led
6_	4000K 102 lm/led
8_	6000K 118 lm/led



SASSO 80 K SPOTLIGHT QR-CBC51 GU5.3	
QR-CBC51 GU5.3	CODE
CAPACITY	060-6129#
1x50W	



SASSO 80 K SPOTLIGHT HIPAR51 GX10	
HIPAR51 GX10	CODE
CAPACITY	060-6629#
1x20W	

Colours



0_...7 white
8 black

Accessories



TRIMLESS OFFSET
Einbauset für randlosen Einbau in Gipskartondecken
Mounting set for trimless installation in plasterboard ceilings
Attrezzo di montaggio per soffitti di cartongesso a scomparsa

Ø/OFFSET/CEILING THICKNESS (MM)	CODE
87/15/8-25	052-193131#



WITH TRIM OFFSET
Einbauung für Zwischendecken von 2-20mm
Mounting ring for intermediate ceilings 2-20mm
Anello di montaggio per controsoffitti di 2 a 20mm

Ø/OFFSET/CEILING THICKNESS (MM)	CODE
97/15/2-25	052-193219#

052-...7 white
8 black



Betoneinbauehäuse für gespachtelte Betondecken
Mounting housing for primed concrete ceilings
Corpo per montaggio in calcestruzzo stuccato

TYPE	L/B/H (MM)	CODE
mounting housing	225/225/130	052-1914310
mount. housing with channel	460/225/130	052-1915310



Elektronischer LED Konverter | Transformator
Electronic LED converter | transformer
Convertitore LED | trasformatore elettronico

CAPACITY	L/B/H (MM)	CODE
4W LED 100-240V	73/40/16	007-1924200
70VA/230-240V/12V	102/51/30	002-70700
105VA/230-240V/12V	102/51/30	002-71000
150VA/230V/12V	206/45/40	002-71500



Vorschaltgeräteblock mit Kabel und Anschlussstecker
Control gear unit with cable and connector plug
Blocco di reattore elettronico con cavo e connettore a spina

CAPACITY	L/B/H (MM)	CODE
20W/220-240V electr.	140/67/31	002-85020



See page 101 for more accessories

RGB LED Inset
Colour and protection filters
Lenses and honeycomb louver

▶ PRIVATE RESIDENCE, WASSENAAR/NETHERLANDS
Architect: Paul Maas, ZONA architectural associates, The Hague
Lighting design: Industrielicht, Alblasserdam

