

**GATE GS & GR.**

Bench system for public areas. Benches available in 3 straight (GS) and 2 curved (GR) basic units. These can be linked to form rows that are straight, curved or at right angles to suit their setting. The benches may be fitted with backrests, and/or seats as required. Standard spacing gives a centre-to-centre seat space of 650 mm, but this spacing may be varied to accommodate more or fewer seats as desired. Benches may be anchored to the floor.

General measurements:

Seat height (bench)	420
Seat height (incl.seat)	455
Depth bench	460
Total depth incl.backrest	585
Seat Ø	390
CC seats	650

Gate straight, GS

GS 20, 2-seat unit	1300
GS 30, 3-seat unit	1950
GS 40, 4-seat unit	2600

Gate round, GR

Radius 1500 mm from centre to outline.

GR 20, 2-seat unit 1/6 circle, 60°

GR 10, 1,5-seat unit 1/8 circle, 45°

Gate GR are add-on units, if GR is used as a free standing unit (not anchored to the floor) you need at least 2 x GR 20 units linked and in a s-shape or 3 x GR 20 units linked to form a semi-circle.

Bench-top of stave-glued solid birch, 40 mm thick. Frame in galvanised or lacquered steel. Upholstered seat covered in leather or fabric. Upholstery in fire retardant polyether foam. Backrest of compression-moulded birch (stained or natural lacquered).

Accessories:**Backrests:**

Round, D20

Straight, D21

Gate seats:

Round upholstered, D25 (suits backrest D20 and D21)

Straight upholstered, D26 (suits backrest D20 and D21)

Whole straight seat D28 (not suitable with backrests)

Whole round seat D27 (not suitable with backrests)

Gate armrests

Bench, backrests and seats can be offered in other materials and designs on request.

Order our complete gate complete Cad library.

Wall/Bench spacer available in galvanised steel.

